ECODESIGN INFORMATION

According to Regulation EU No 327/2011 of the European Commission, implementing Directive 2009/125/CE of European Parliament
Apply to fans

SODECA, S.L.U. www.sodeca.com

ERP: Performance at the best efficiency point (BEP)

MC	Measurement category	**[m^3/h]**	Flow rate	**ηe [%]**	Efficiency
EC	Efficiency category	**[Pa]**	Static pressure / Total pressure	**N**	Efficiency grade
VSD	Variable Speed Drive	**[RPM]**	Speed	**[kw]**	Input power
SR	Specific ratio				

Model	MC	EC	VSD	SR	ηe[%]	N	[kW]	[m^3/h]	[Pa]	[RPM]
PF/EC-H-1031-4M-0.33 IE5	A	Static	VSD built-in to the fan	1.00	63.9	82.4	0.173	1413	25	1500
PF/EC-H-1031-4T-0.33 IE5	A	Static	VSD built-in to the fan	1.00	63.9	82.4	0.173	1413	25	1500
PF/EC-H-1135-4T-0.5 IE5	A	Static	VSD built-in to the fan	1.00	67.9	83.9	0.297	2076	32	1500
PF/EC-V-1031-4M-0.33 IE5	A	Static	VSD built-in to the fan	1.00	63.9	82.4	0.173	1413	25	1500
PF/EC-V-1031-4T-0.33 IE5	A	Static	VSD built-in to the fan	1.00	63.9	82.4	0.173	1413	25	1500
PF/EC-V-1135-4T-0.5 IE5	A	Static	VSD built-in to the fan	1.00	67.9	83.9	0.297	2076	32	1500